



Aluminium column SAL-P81

diameter Ø180mm at the base plate



Code	Symbol	Height of the kolumn	Wall thickness	Net weight	Approximate unit volume	Concrete footing / reinforcement basket type	Concrete footing / reinforcement basket code	Fasteners
42489	SAL-P81	10,3m	4,3mm	58,8kg	0,803m ³	B-71 / Z-71	311170 / 311207	4012

SAL-P81	Acceptable windage of single luminaire [m 2] for Cx=0,7			
code 42489	Vref. = 22 m/s	Vref. = 24 m/s	Vref. = 26 m/s	Vref. = 28 m/s
Permissible weight of a single luminaire	I zone, II Field category up to	I & III zone, II Field category up to 450m by s.l	II zone, II Field category up to	III zone, II Field category up to 755m by s.l
15	0,44	0,33	0,18	0,13

SAL-P81	Acceptable windage of single luminaire [m 2] for Cx=0,7			
code 42489	Vref. = 22 m/s	Vref. = 24 m/s	Vref. = 26 m/s	Vref. = 28 m/s
Permissible weight of a single luminaire	I zone, II Field category up to	I & III zone, II Field category up to 450m by s.l	II zone, II Field category up to	III zone, II Field category up to 755m by s.l
15	0,28	0,19	x	x

- Anodising:** 10 colours, each with possibility of chemical brightening
- Finish:** grinded, anodisedaluminium, option of elastomer protection in the colour of the column up to the height of 350 mm (other height on customer's request)
- Luminaire mounting:** directly on the column, luminaires with mounting Ø60mm mm with weight and surface parameters not exceeding the data from the strength table included in the technical data sheet
- Extension arm type:** According to resistance calculations
- Packing:** sleeve material